

EWAG INFO 5/2019

# RETROFIT – SUCTION WS 11 / WS 11-SP

For grinding dust suction and filtration  
Stepless adjustment of the suction capacity



## Benefit

We offer you a retrofit kit that converts your existing machine with little effort into an easy-to-use grinder which corresponds to the current regulations for dust filtration.

# RETROFIT – grinding dust suction and filtration

## Advantages:

- Corresponds to the current official health regulations (HEPA H14)
- The suction capacity is infinitely variable according to the grinding application.

## TBH filter device FP150

Free-standing

- Max. flow rate 280 m<sup>3</sup>/h
- Max. negative pressure 20.000 Pa
- Nominal capacity 30–250 m<sup>3</sup>/h at 15.000 Pa
- Electronic volume flow controller
- Filter contamination display
- 3-stage filter module which meets the official legal requirements (HEPA H14)
- Can be placed in a separate room (max. distance approx. 3m)



## ULT filter device ASD 160 MD13 H14

integrated (depending on the model of your WS11/WS11-SP, on the front or the back side)

- Max. flow rate 250 m<sup>3</sup>/h
- Max. negative pressure 7.500 Pa
- Nominal capacity 180 m<sup>3</sup>/h at 2.700 Pa
- Electronic volume flow controller
- Filter contamination display
- 3-stage filter module which meets the official legal requirements (HEPA H14)



**Are you interested?**

**Contact us!**

Ewag AG

Industriestrasse 4 · 4554 Etziken, Switzerland

Tel. +41 32 613 31 31 · Fax +41 32 613 31 15

info@ewag.com · www.ewag.com

